



Technical datasheet No.: **1040.2**
Product: POLYMAR® Side Curtain
Article No.: 8556 5240

Type of coating and finish			
Type of coating	PVC		
Finish	both sides lacquered, high gloss		
Flame retardancy	DIN 75200, ISO 3795 <100 mm/min.		
Total weight	900 g/m ²	EN ISO 2286-2	
Tensile strength (warp/weft)	4300 / 4000 N/50 mm	DIN 53354, DIN EN ISO 1421/V1	
Tear strength (1) (warp/weft)	500 / 500 N	DIN 53363	
Adhesion (1)	20 N/cm	LB 3.04-1 (Complan)	
Cold resistance	- 30 °C	DIN 53361	
Heat resistance	+70 °C	Complan-Richtlinie	
Light fastness	>6 Note	DIN 54004, DIN EN ISO 105 B02	
Crack resistance (1)	no cracks	< 100000 x	DIN 53359 A
Base fabric			
Material	PES	DIN ISO 2076	
Yarn count	1100 dtex	DIN ISO 2060	
Weave	P 2/2		
Remarks	complies with DIN EN 12941-2, materials		

These indicated technical data are based on average results. Due to production procedures slight deviations can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products.